


技术参数

声光介质
 声波模式
 声速
 波长
 输入偏振
 输出偏振
 插入损耗
 中心频率
 射频带宽
 射频驱动功率
 通光孔径
 平均衍射效率
 带宽内光强变化
 最小衍射效率
 峰值@633 nm
 RMS at 633 nm
 驻波比
 扫描角
 时间带宽积

TeO₂
 Longitudinal
 4.20 mm/μs
 1066-1100 nm
 Random
 Random
 <3%
 100 MHz
 50MHz, goal 60MHz
 8W*
 4mm dia.
 N/A
 N/A
 70%
 N/A
 N/A
 2.0:1
 >0.75 degree
 N/A

外观尺寸图



Notes:

1. Input Impedance is 50 Ohms.
2. Electrode: Two Element Phased Array
3. MTBF 3500 hours with a 500W laser and a 1.5mm 1/e² beam diameter. Lifetime limited by bulk optical damage.

*water cooled



Document

07/20/16

Control

THIS DOCUMENT IS THE PROPERTY OF GOOCH & HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH & HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH & HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	Geri Scholz 7/14/2016	Gooch & Housego		
MATERIAL:	CHK		DESCRIPTION: AODF 4100-6		
FINISH: 	APP		PART NUMBER:	REV:	SHEET 1 OF 1
	APP		97-03120-02	5	