


技术参数

声光介质	TeO2
声波模式	Shear, Off Axis
声速	0.710 mm/μs
波长	442 nm
输入偏振	0° to Mounting Plane
输出偏振	90° to Mounting Plane
插入损耗	5%
中心频率	200 MHz
射频带宽	100 MHz
射频驱动功率	1.0 Watt
通光孔径	4.8 mm
平均衍射效率	>75%
带宽内衍射效率平坦度	±10%
最小衍射效率	>70%
峰值@633 nm (无射频功率时)	< 0.100
RMS at 633 nm	N/A
驻波比	< 2.0:1
扫描角	63.1 mrad @ 442 nm
时间带宽积	N/A

外观尺寸图



Notes:

1. Input impedance is 50 Ohms.
2. Anti-Reflection Coating is less than 1.0% both side.
3. Time Aperture is 6.5 us.



Document

06/08/18

Control

THIS DOCUMENT IS THE PROPERTY OF GOOCH & HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH & HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH & HOUSEGO.

TOLERANCES: .XX ± .25 .XXX ± .125	DR	Geri Scholz 6/4/2018	Gooch & Housego	
MATERIAL:	CHK		DESCRIPTION: AODF 4200-1	
FINISH: 	APP		PART NUMBER:	97-01610-51
	APP		REV:	A
				SHEET 1 OF 1