

技术参数

声光介质	Crystalline Quartz
声速	5.74 mm/μs
通光孔径*	1.5 mm 'H'
中心频率	40.68 MHz
射频带宽	2 MHz @ -9 dB Return Loss
输入阻抗	50 Ohms Nominal
驻波比	1.2 :1 Max
工作波长	1064 nm
插入损耗	1 % Max
单面反射率	0.1 % Max
增透镀膜标准	MIL-C-48497
光功率密度	500 MW/cm ²
消光比	1000 :1 Min
偏振	90 ° To Mounting Plane

波长性能参数

工作波长 (nm)	1064
射频驱动功率(W)	20
布拉格角(mr)	3.8
光束分离角 (mr)	7.6

光束直径性能参数

光束直径 (μm)	375
对应工作波长 (nm)	1064
	NA
上升时间 (nsec)	50
调制带宽	NA
光束椭圆度	NA


特殊测试项目

	Min	Units	Max
损耗调制	90	%	
最大射频功率			20W

*通光孔径：器件中适用于规定性能指标的有效通光孔径范围。

外形尺寸图:

Package 97-03279-01-15rA



Document

08/07/15

Control

Notes:

Optical path 30mm; conduction cooled through base.
Optical window parallelism <1 arc minute.
MECHANICAL OUTLINE PER 97-03279-01-15
Optical power density for 20nsec pulses



THIS DOCUMENT IS THE PROPERTY OF GOOCH AND HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES GOOCH AND HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH AND HOUSEGO.

TOLERANCES: .XX ± .01 .XXX ± .005	DR	Tom Ng 8/6/2015	Gooch & Housego	
MATERIAL:	CHK	RoHS	DESCRIPTION: AOQS 5041-290	
FINISH:	APP	Compliant	30mm, SMA 6", ROHS	
	APP		PART NUMBER: 97-03279-01	REV: A
				SHEET 1 OF 1