

DATA SHEET

S6EXZ9313-684

BEAMEXPANDER


MAGNIFICATION 1.0 - 3.0

FOR 9300 nm

ZnSe



outline drawing



DATA SHEET

specifications

article number	S6EXZ9313-684
design wavelength [nm]	9300
magnification factor	1.0 - 3.0
divergence adjustable	yes
optical principle	Galilei (no internal focus)
pointing stability [mrad]	< 1
clear input aperture [mm]	28.5
clear output aperture [mm]	45.0
max. input beam-Ø [mm] ¹⁾	16.7 (1x) - 8.9 (3x)
total number of lenses	3
total transmission [%]	> 97
lens material	ZnSe
LIDT (coating) [J/cm²]	max. power 500 W
SP and USP usable	no
SP and USP usable, reversed usage	no
mounting thread	M55x1
weight [kg]	1.4
accessory	---

remarks

¹⁾clipped at $1/e^2$

magnification (reversed mode) = $1 / \text{magnification (regular mode)}$

divergence adjustment = 0 → collimated input beam results in collimated output beam


maximum divergence adjustment is $\pm 3 \text{ mm}$

RoHS compliant


length at divergence setting „0“ stated in the drawing - length extension of max. 3 mm is possible

max vignetting of 1.0%

divergence adjustment



mounting positions



back reflection position

back reflections [mm]	
0.0	
back reflections reverse [mm]	
122.3	
0.00	
0.00	

新特光电是 Sill Optics 在中国及东南亚地区的官方授权合作伙伴。

您可通过 Sill Optics 官网查阅授权资质: <https://www.silloptics.de/unternehmen/vertriebspartner>, 新特光电持有 Sill Optics 官方出具的正式授权证书, 如有必要欢迎联系我司市场销售人员查阅。我们一站式提供 Sill Optics 各类光学元件的选型、方案设计及集成支持, 覆盖全生命周期服务, 满足科研与工业客户需求。更多信息请访问: www.SintecLaser.com

获取最新方案及报价, 请手机/微信联系: 罗经理: 18162698939, 程经理: 18162698959, 夏经理: 13697356016